### SAFETY DATA SHEET

#### 1. Identification

Product identifier DEFEND

Company information CONTINENTAL RESEARCH CORPORATION

P.O. Box 15204

St. Louis Mo 63110 United States

Company phone 800-325-4869

**Emergency telephone US** 888-255-3924 (CHEM-TEL)

Version # 01

Recommended use Pesticide Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Health hazards Sensitization, skin Category 1 Aspiration hazard

**Environmental hazards** Not classified. OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. May cause an allergic

skin reaction.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

> flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Contaminated work clothing must not be allowed out of the workplace. Wear

Category 1

protective gloves.

Response If swallowed: Immediately call a poison center/doctor, If on skin: Wash with plenty of water,

Specific treatment (see this label). Do NOT induce vomiting. If skin irritation or rash occurs: Get

medical advice/attention. Wash contaminated clothing before reuse. Collect spillage.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	% 10 - 20	
Distillates (Petroleum), Hydrotreated Light		64742-47-8		
Butane	106-97-8		2.5 - 10	
Propane		74-98-6	2.5 - 10	

Product name: Defend SDS US Issue date: 05-14-2015 1/10

Chemical name	Common name and synonyms	CAS number	%
White Mineral Oil		8042-47-5	1 - 2.5
Permethrin		52645-53-1	
Other components below reportable le	evels	***************************************	60 - 80

<sup>#:</sup> This substance has workplace exposure limit(s).

### 4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Get medical attention if irritation develops or persists. In case of eczema or other skin disorders:

Seek medical attention and take along these instructions.

Eye contact

Ingestion

After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician or Poison Control Center immediately. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of a large amount does occur, seek medical attention. Do not give milk, alcoholic

beverages or castor oil.

Most important symptoms/effects, acute and delayed

Dermatitis. Aspiration may cause pulmonary edema and pneumonitis. Rash. May cause an allergic skin reaction.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Powder, Alcohol resistant foam, Dry chemicals, Carbon dioxide (CO2),

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Product name: Defend

SDS US Issue date: 05-14-2015

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.

#### Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

#### Precautions for safe handling

Will ignite if exposed to intensive heat or open air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Keep away from food, drink and animal feedingstuffs. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

## 8. Exposure controls/personal protection

#### Occupational exposure limits

Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm	
US. ACGIH Threshold Limit Value Components	es Type	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	<del>"</del>
US. NIOSH: Pocket Guide to Che Components	mical Hazards Type	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	

#### **Biological limit values**

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

Eye/face protection Face s

Face shield is recommended. Wear safety glasses with side shields (or goggles). Avoid contact with eyes.

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Product name: Defend issue date: 05-14-2015

Other

Avoid contact with the skin. Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Chemical resistant gloves. Choose body protection according to the

amount and concentration of the dangerous substance at the work place.

Skin protection

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

Appearance

Physical state

Gas.

Form

Aerosol.

Color

White.

Odor threshold

None known.

Not available.

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling

Not available.

range

Odor

Ηq

Flash point

-156.0 °F (-104.4 °C) Propellant estimated

**Evaporation rate** 

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.9 % estimated

(%)

Flammability limit - upper

9.5 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available. 70 - 85 psig @70F estimated

Vapor pressure Vapor density

Not available.

Relative density

Not available

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

Not available.

(n-octanol/water)

Not available.

Auto-ignition temperature Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Specific gravity

0.863 estimated

## 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Risk of ignition.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air. Heat, flames and sparks. Avoid temperatures exceeding the flash point. Do not

mix with other chemicals. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Nitrates, Oxygen, Fluorine, Chlorine,

Product name: Defend Issue date: 05-14-2015

SDS US

Hazardous decomposition products

May include oxides of phosphorus. No hazardous decomposition products are known.

### 11. Toxicological information

## Information on likely routes of exposure

Ingestion

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Inhalation

Not available.

Skin contact

May cause an allergic skin reaction.

Eve contact

Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dermatitis. Aspiration may cause pulmonary edema and pneumonitis. Rash. Direct contact with

eyes may cause temporary irritation. May cause an allergic skin reaction.

Information on toxicological effects

**Acute toxicity** 

Acute LD50: 12479 mg/kg, Rat, Dermal Acute LC50: 32 mg/l/4h, Rat, Inhalation

May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

**Product** Species **Test Results** Defend (CAS Mixture) Acute Dermal LD50 Rat 12479 mg/kg Inhalation LC50 Rat 32 mg/l/4h Components **Species Test Results** Butane (CAS 106-97-8) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8) Acute Dermal LD50 Rabbit > 2000 mg/kg > 2000 mg/kg, 24 Hours Inhalation LC50 Rat > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours Oral LD50 Rat > 5000 mg/kg Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l 658 mg/l/4h White Mineral Oil (CAS 8042-47-5) Acute Dermal

Product name: Defend Issue date: 05-14-2015

LD50

Rabbit > 2000 mg/kg, 24 Hours

SDS US

Components Test Results

Inhalation

LC50

Rat

2.18 mg/l, 4 Hours

Oral

LD50

Rat

5000.0001 mg/kg

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Not expected to be hazardous by OSHA criteria.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not available.

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by WHMIS criteria.

Carcinogenicity

Not expected to be hazardous by WHMIS criteria. This product is not considered to be a

carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Permethrin (CAS 52645-53-1)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by WHMIS criteria.

Specific target organ toxicity -

single exposure

Not classified

Specific target organ toxicity -

repeated exposure

Not classified

Aspiration hazard

May be fatal if swallowed and enters airways.

Chronic effects

Not expected to be hazardous by WHMIS criteria.

Further information

This product has no known adverse effect on human health.

### 12. Ecological information

**Ecotoxicity** 

Product

LC50: 280 mg/L, Fish, 96.00 Hours

Species

Very toxic to aquatic life with long lasting effects.

- Toduci		Species	Test Results
Defend (CAS Mixture	e)		
Aquatic			
Fish	LC50	Fish	280 mg/L, 96 Hours
Components		Species	Test Results
Distillates (Petroleum)	), Hydrotreated Ligh	t (CAS 64742-47-8)	
Aquatic	•	.,	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Permethrin (CAS 526	45-53-1)	, ,	
Aquatic	·		
Crustacea	EC50	Water flea (Daphnia magna)	0.0006 - 0.0025 mg/l, 48 hours
Fish	LC50	Apache trout (Oncorhynchus gilae apache)	0.0013 - 0.0022 mg/l, 96 hours
White Mineral Oil (CA	S 8042-47-5)		
Aquatic	,		
Físh	LC50	Fish	10000.0001, 96 Hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Partition coefficient n-octanol / water (log Kow)

Butane Permethrin Propane

2.89 6.5 2.36

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

Disposal instructions

Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds,

waterways or ditches with chemical or used container. After recovery of solvent dispose of residue as hazardous waste. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

## 14. Transport information

#### DOT

**UN** number

UN 1950

UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

Class

2.1

Subsidiary risk Label(s)

2.1

Packing group

Not applicable.

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions

306 None

Packaging non bulk Packaging bulk

None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

**UN number** 

UN1950

UN proper shipping name

Aerosois, flammable

Transport hazard class(es)

Class

2.1

Subsidiary risk Label(s)

2.1

Packing group

Not applicable.

Environmental hazards **ERG Code** 

Yes 101

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Cargo aircraft only **Packaging Exceptions** 

Allowed. LTD QTY

**IMDG** 

**UN number** 

UN1950

Product name: Defend Issue date: 05-14-2015

SDS US

UN proper shipping name Transport hazard class(es)

**AEROSOLS** 

Class

Subsidiary risk Label(s)

2.1

Packing group

2.1

Not applicable.

**Environmental hazards** 

Marine poliutant

Yes

**EmS** 

F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** Transport in bulk according to

LTD QTY Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Product name: Defend Issue date: 05-14-2015

## SARA 304 Emergency release notification

Not regulated.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No. Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

## SARA 313 (TRI reporting)

Chemical	name

CAS number

% by wt.

Permethrin

52645-53-1

0.1 - 1

### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

FIFRA Information

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The pesticide label also includes other important information, including directions for use.

US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

# US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

# US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

# US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

### US. Rhode Island RTK

Butane (CAS 106-97-8) Permethrin (CAS 52645-53-1) Propane (CAS 74-98-6)

### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region Australia Canada Canada China Europe	Inventory name Australian Inventory of Chemical Substances (AICS) Domestic Substances List (DSL) Non-Domestic Substances List (NDSL) Inventory of Existing Chemical Substances in China (IECSC) European Inventory of Existing Commercial Chemical Substances (FINECS)	On inventory (yes/no)* Yes Yes No Yes No
China	Non-Domestic Substances List (NDSL) Inventory of Existing Chemical Substances in China (IECSC)	

Product name: Defend Issue date: 05-14-2015

Country(s) or region	Inventory name	On inventory (see to st
Europe	European List of Notified Chemical Substances (ELINCS)	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
	(PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Yes \*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date

05-14-2015

Issued By

**EHS Administrator** 

Version #

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Product name: Defend

Issue date: 05-14-2015