

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: DICHLORODIFLUORO METHANE

SAP Material No: NM9520

General or Generic ID: HALOGENATED HYDROCARBON

Company

Telephone Numbers

The Valvoline Company

Emergency: 1-800-274-5263

P.O. Box 14000

Lexington, KY 40512

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)

CAS Number

% (by weight)

DICHLORODIFLUORO METHANE

75-71-8

100.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation.

Skin

Causes burns and frostbite.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

NFR1001

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects

No data

Developmental Information

No data

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact.

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

NFR1001

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

Skin

Treat burned or frostbitten skin by flushing the exposed area with lukewarm water. Seek immediate medical attention.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting.

FIRE FIGHTING MEASURES

Flash Point

Not applicable

Explosive Limit

Not applicable

NFR1001

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbonyl fluoride, hydrogen chloride, hydrogen fluoride
phosgene.

Fire and Explosion Hazards

No special fire hazards are known to be associated with this
product.

Extinguishing Media

Use an extinguishing media appropriate for surrounding fire..

Fire Fighting Instructions

Water may be used to keep fire-exposed containers cool until fire
is out. Wear a self-contained breathing apparatus with a full
facepiece operated in the positive pressure demand mode with
appropriate turn-out gear and chemical resistant personal
protective equipment. Refer to the personal protective equipment
section of this MSDS.

NFPA Rating

Health - 1, Flammability - 0, Reactivity - 1

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Allow to evaporate. Ventilate area.

Large Spill

Allow to evaporate. Persons not wearing protective equipment
should be excluded from area until leak has been repaired.

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

7. HANDLING AND STORAGE**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. This is a high-pressure gas. Use piping and equipment adequately designed to withstand pressures to be encountered. Use with adequate ventilation. Close valve when not in use and when cylinder is empty. Always use a suitable hand truck or similar device for moving gas cylinders. Firmly secure cylinders during transport. Do not lift or move a cylinder by the cap. Do not roll or drag a cylinder to move it or allow cylinders to strike each other or any surface violently. Never tamper with or attempt to repair or alter cylinders, valves or any safety relief devices. Do not attempt to remove a stuck cap by using a lever in the cap ports. This may accidentally open the valve when the cap turns. Never work on a pressurized system. If there is a leak, close the cylinder valve, blow down the system by venting to a safe place, and then repair the leak. Be sure to read and understand all labels and other instructions supplied with all containers of this product. For safety information on general handling of compressed gas cylinders, it is recommended that a copy of Pamphlet P-1, Safe Handling of Compressed Gases in Containers, be obtained from the Compressed Gas Association, Inc.

Storage

Store cylinders upright and secured in a well-protected, well-ventilated, dry location away from heavy traffic and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125 degrees F (52 degrees C). Store cylinders at least 20 feet away from highly combustible materials, and away from any sparks, flames, or any other source of heat or ignition. Protect cylinders from physical damage. Assigned storage places should be located where cylinders will not be knocked over or damaged by passing or falling objects. Segregate full and empty cylinders. Prevent full cylinders from being stored for excessive periods of time. If gas cylinders were designed to have valve caps, keep caps on and hand-tight at all times when cylinders are not in use or connected for use. Caps are for valve protection ONLY.

NFR1001

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves such as: polyvinyl alcohol, Wear normal work clothing covering arms and legs..

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

DICHLORODIFLUORO METHANE (75-71-8)

OSHA VPEL 1000.000 ppm - TWA

NIH TLV 1000.000 ppm - TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for product) -21.6 F (-29.7 C) @ 760.00 mmHg

NFR1001

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

Vapor Pressure

(for product) 4700.000 mmHg @ 77.00 F

Specific Vapor Density

4.300 @ AIR=1

Specific Gravity

1.315 @ 77.00 F

Liquid Density

10.950 lbs/gal @ 77.00 F

1.315 kg/l @ 25.00 C

Percent Volatiles (Including Water)

100.0 %

Evaporation Rate

FASTER THAN ETHYL ETHER

Appearance

No data

State

GAS

Physical Form

HOMOGENEOUS SOLUTION

Color

CLEAR & COLORLESS

Odor

No data

Not applicable

NFR1001

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbonyl fluoride, hydrogen chloride, hydrogen fluoride
phosgene.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: alkali metals, powdered metals.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Return to supplier for reclamation.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

DICHLORODIFLUOROMETHANE, 2.2, UN 1028

NFR1001**MATERIAL SAFETY DATA SHEET**

The Valvoline Company

Page 009

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

5000

DICHLORODIFLUOROMETHANE

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4

Component

Component

DICHLORODIFLUOROMETHANE

5000

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire() Reactive() Sudden

Release of Pressure(X)

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)

CAS Number

DICHLORODIFLUOROMETHANE (CFC-12)

75-71-8

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 010

Date Prepared: 07/06/00

Date Printed: 05/01/02

MSDS No: 999.0016534-007.011

DICHLORODIFLUORO METHANE

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

DICHLORODIFLUOROMETHANE

75-71-8

Pennsylvania RTK Label Information

METHANE, DICHLORODIFLUORO-

75-71-8

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.