



## MATERIAL SAFETY DATA SHEETS (MSDS) On-Line OSHA-Required Health And Safety Information!

### Section 1

#### MATERIAL SAFETY DATA SHEET # 70

#### Hercules Purple PVC Primer

Date Prepared: 24-Mar-94

Last Reviewed: 01-Jul-98

Hercules Chemical Co, Inc.

111 South Street

Passaic, NJ 07055-7398

Tel (800) 221-9330

Fax (800) 333-3456

E-Mail [info@herchem.com](mailto:info@herchem.com)

Meets OSHA 29 CFR 1910.1200

### Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s), CAS Numbers)	OSHA PEL	ACGIH TLV	Other Limits	% Upper Bound Limits if SARA Reportable
<i>[AF]=Alternative Acetone Formula. Examine product label to determine which formula is involved.</i>				
Tetrahydrofuran (109-99-9)	200PPM	200PPM	N/A	--
Methyl Ethyl Ketone (78-93-3)	200PPM	200PPM	N/A	85%
Cyclohexanone (108-94-1)	25PPM	25PPM	N/A	--
Tetrahydrofuran (109-99-9)[AF]	200PPM	200PPM	N/A	--
Methyl Ethyl Ketone (78-93-3)[AF]	200PPM	200PPM	N/A	40%
Cyclohexanone (108-94-1)[AF]	25PPM	25PPM	N/A	--
Acetone (CAS 67-64-1)[AF]	1000 PPM	750 PPM	N/A	45%

**HMIS Hazard Rating:** Health: 3 Flammability: 4 Reactivity: 1 Personal Protection: G

### Section 3 - Physical/Chemical Characteristics

<b>Boiling Point (°F):</b>	<b>Specific Gravity (H<sub>2</sub>O=1):</b>	<b>Vapor Density (Air=1):</b>	<b>Vapor Pressure (mm Hg):</b>
133 Based on first boiling component-Acetone	0.820 ± 0.03	2.0 to 2.5	190 Based on first boiling component-Acetone
<b>Melting Point (°F):</b>	<b>Evaporation Rate (Butyl Acetate=1):</b>	<b>Solubility in Water:</b>	

N/A

7-11

50% to 75%

Appearance And Color: Purple Liquid

Odor: Ethereal &amp; Acetone-like

**Section 4 - Fire And Explosion Hazard Data****Flash Point:**

0° to 6.0 °F (TCC) (Based on acetone)

**Flammable Limits:****LEL:**

2%

**UEL:**

13.0%

**Extinguishing Media:** Foam/Dry Chemical/CO2**Special Firefighting Procedures:**

Handle as flammable liquid. Wear self-contained breathing apparatus &amp; chemical goggles. Water may be ineffective, but should be used to keep fire-exposed containers cool.

**Unusual Fire And Explosion Hazards:**

Vapor is heavier than air and travels considerable distance to sources of ignition and flashback. On long standing may cause peroxides which may cause violent reaction especially upon evaporation to dryness.

**Section 5 - Reactivity Data****Stability:** Stable**Conditions To Avoid:** Keep in closed containers away from sparks and open flame.**Incompatibility  
(Materials To Avoid):**

Strong oxidizing materials, Lithium Aluminum Hydride, Sodium Aluminum Hydroxide, Sodium &amp; Potassium Hydroxides.

**Hazardous  
Decomposition:**

Carbon dioxide and carbon monoxide are formed. Irritating peroxide fumes are formed when heated to decomposition.

**Hazardous  
Polymerization:**

Avoid excessive exposure to air and cationic initiators like Lewis Acids.

**Section 6 - Health Hazard Data****Routes of Entry:****Inhalation?** YES/Primary**Skin?** YES/Primary**Ingestion?** YES/Secondary**Health Hazards:**

Corrosive to eyes and skin irritant. Severe overexposure can cause headache, dizziness and narcosis. May cause dermatosis and dermatitis with prolonged repeated contact.

**Carcinogenicity:****NTP?** NO**IARC?** NO**OSHA Regulated?** NO**Signs And Symptoms of Exposure:**

INGESTION: No effects expected. INHALATION: Will cause irritation of mucous membranes, nose, eyes, &amp; throat; coughing, difficulty of breathing. Exposure to high vapor concentration may cause headache, dizziness, nausea, narcosis. SKIN CONTACT: Prolonged skin contact causes common solvent defatting effect. EYE CONTACT: Vapors slightly uncomfortable. Splashes irritating. Will cause painful burning or stinging of eyes &amp; lids, watering of eyes and Conjunctiva.

**Medical Conditions Generally Aggravated By Exposure:**

No data found

**Emergency And First Aid Procedures:**

INGESTION: DO NOT INDUCE VOMITING. If conscious, dilute by giving 2 glasses of water. Call a physician immediately. INHALATION: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth resuscitation. If breathing is difficult, give oxygen. Call a physician. SKIN

**CONTACT:** Wash affected area with soapy water. Remove contaminated clothing. **EYE CONTACT:** Immediately flush eyes with plenty of water for 15 minutes. Consult a physician.

### Section 7 - Precautions For Safe Handling And Use:

**Steps To Be Taken In Case Material Is Released Or Spilled:**

Eliminate sources of ignition. Absorb with sand or inert absorbing material. Dispose of with solid waste in accordance with all regulations. Flush spill area with water. Avoid flushing into confined areas.

**Waste Disposal Method:**

Incinerate in accordance with federal, state and local regulations.

**Precautions To Be Taken In Handling And Storing:**

Store in cool, well-ventilated area. Keep away from open flame and sources of ignition.

**Other Precautions:**

Use normal good personal hygiene.

### Section 8 - Control Measures:

<b>Respiratory Protection:</b>	In confined spaces or other circumstances where adequate ventilation cannot be assured use NIOSH-approved respirator, positive pressure airline mask, or self contained breathing apparatus.		
<b>Ventilation:</b>	<b>Local</b>	As required	<b>Special:</b> When using cements in an area of
	<b>Exhaust:</b>	All ventilating devices	<b>Other:</b> limited ventilation, use a ventilation
	<b>Mechanical:</b>	must be located so they do not provide a source of ignition.	device such as a fan or air mover to maintain a safe air concentration.
			N/A
<b>Gloves:</b>	PVA gloves		
<b>Eye Protection:</b>	Chemical Safety goggles.		
<b>Other Protective Clothing:</b>	Apron, boots, eye bath, safety shower		
<b>Work/Hygienic Practices:</b>	Wash thoroughly after handling. Avoid ingestion of the cements. do not eat or drink when using cements or in the vicinity where such cements are being used.		

| [Home Page](#) |

| [MSDS](#) | [Wholesaler Info](#) | [Contractor Info](#) | [Homeowner & Industrial Info](#) |

Hercules Chemical Co, Inc.  
111 South Street  
Passaic, NJ 07055-7398  
Tel 1-800-221-9330

Fax 1-973-777-4115  
E-Mail [info@herchem.com](mailto:info@herchem.com)

---

*WWW Pages - developed by Hercules Chemical Co. Inc.  
For more info send E-Mail to [info@herchem.com](mailto:info@herchem.com)  
©Hercules Chemical Comp., Inc. All Rights Reserved.*