

MATERIAL SAFETY DATA SHEET

Effective Date: none

Revision Date: none

NAPA Tire Mounting & Rubber Lubricant (Plastic, 1 Gallon)

Code: AGS

Page: 1

Section 1 - Product and Company Identification

PRODUCT NAME: NAPA Tire Mounting & Rubber Lubricant (Plastic, 1 Gallon)

MANUFACTURER'S NAME:

AGS Company
2651 Hoyt St.
Muskegon Hts. , MI 49444

EMERGENCY TELEPHONE NUMBER

MISCELLANEOUS INFORMATION
(616) 733-2101

Section 2 - Hazardous Ingredients

HAZARDOUS INGREDIENT	CAS NO.	WGT. %	TLV
Potassium Vegetable			
Oil Soap	N/Applicable	5-15	Not known
Ethylene Glycol *	107-21-1	1.3	10 cu. m. or 50 ppm

NOTE: * The following chemical is listed in Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Section 3 - Hazards Identification

EYES: May cause irritation, discomfort and pain.

SKIN: May cause irritation or dermatitis.

INGESTION: May cause nausea and/or diarrhea. Ingestion may also cause depression followed by respiratory and cardiac failure.

INHALATION: May cause irritation.

OTHER EFFECTS: Vaporizing solution may cause inhalation effects such as CNS depression and hematopoietic dysfunction.

Section 4 - First Aid Measures

EYES: Flush with water for at least 15 minutes. Get medical attention.

SKIN: Wash effected area. Remove contaminated clothing. If adverse effects occur, consult a physician.

INGESTION: May cause nausea, diarrhea, renal or brain damage, respiratory and cardiac failure.

INHALATION: Remove to fresh air. Administer oxygen or artificial respiration as needed, consult a physician.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: none

Revision Date: none

NAPA Tire Mounting & Rubber Lubricant (Plastic, 1 Gallon)

Code: AGS

Page: 2

=====

Section 5 - Firefighting Measures

FLASH POINT : Not Applicable

METHOD :

AUTO IGNITION TEMP: Not Applicable

FLAMMABLE LIMITS:

LEL: Not Applicable

UEL: Not Applicable

EXTINGUISHING MEDIA: Not Applicable

SPECIAL PROCEDURES: None

UNUSUAL HAZARDS: None

=====

Section 6 - Environmental Release Measures

SPILL PROCEDURE: Absorb in inert material. Flush residue with water.

=====

Section 7 - Handling and Storage

CONDITIONS TO AVOID: None known.

=====

Section 8 - Exposure Controls/Personal Protection

VENTILATION REQUIREMENTS: General room ventilation is sufficient.

EYES : Yes

GLOVES : Yes

CLOTHING : No

RESPIRATORY: No

OTHER: Eye wash in area.

=====

Section 9 - Physical and Chemical Properties

pH SUPPLIED : 9.6

pH DILUTED : Not Applicable

WATER SOLUBILITY: Complete

SPECIFIC GRAVITY: (Water=1) 1.01 @ 15.5/15.5C

MELTING POINT : Not Applicable

BOILING POINT : 200F

% VOLATILES : 90% (by weight)

VAPOR PRESSURE : Not Determined

VAPOR DENSITY : (Air=1) >1

EVAPORATION RATE: Not Determined

APPEARANCE : Amber liquid with characteristic odor.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: none

Revision Date: none

NAPA Tire Mounting & Rubber Lubricant (Plastic, 1 Gallon)

Code: AGS

Page: 3

=====

Section 10 - Stability and Reactivity

UNSTABLE AND/OR AUTO REACTIVE: Stable

INCOMPATIBLE MATERIALS: Oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

=====

Section 11 - Toxicological Information

Not available.

=====

Section 12 - Ecological Information

Not available.

=====

Section 13 - Disposal Considerations

DISPOSAL METHOD: Removal by an approved, licensed waste hauler.

EPA WASTE I.D. NO.: Not. Reg.

=====

Section 14 - Transport Information

Not available.

=====

Section 15 - Regulatory Information

Not available.

=====

Section 16 - Other Information

TRADE NAME : NAPA Tire Mounting and Rubber Lubricant

COMMON NAME : RuGlyde

CONTAINER SIZE: Plastic, 1 Gallons

NFPA: HEALTH : 1
FLAMMABILITY : 0
REACTIVITY : 0
SPECIFIC HAZARD: N/AHMIS: HEALTH : 1
FLAMMABILITY : 0
REACTIVITY : 0
PROTECTIVE EQUIPMENT: A***The information herein is given in good faith,
no warranty, expressed or implied, is made.***