



#011

Non-Flammable Cleaning Solvent



use that requires quantities of product to be spread over large surfaces (more than 4 square feet). The potential for fire or health effects is increased dramatically.

Description: Non Flammable Cleaning Solvent

Flammability: Non Flammable

Open Time: NA

Clean Up: NA

Shelf Life: One year in closed container.

Limitations: Freeze Proof

Packaging: 1 Gallon (6/case) • 1 Quart (12/case)

Use To Clean: • Oil • Carpet Adhesive
• Carpet Seam Adhesives

Directions: Use only in well ventilated area. To Clean Stains: Using a dry cloth remove as much adhesive as possible before it hardens. Always use a clean, white cloth when using cleaning solvent. Apply cleaning solvent to cloth. Do not pour directly onto stain or adhesive. If carpet is saturated, the solvent it will break down the latex in carpet backings and result in carpet fibers (tufts) releasing or carpet backing delamination. Rub the stained area with the dampened cloth, gently at first. If this does not seem to effect the stain, rub more vigorously. Allow cleaned area to dry thoroughly before allowing traffic. To Clean

Tools: Soak tools in cleaning solvent and then wash with soapy water. Dry with a cloth. This is a cleaning solvent. If this product will be used for any other purpose, contact Capitol Adhesives prior to use.

FIRST AID: Caution: Avoid inhalation of solvent fumes. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If on skin: wash thoroughly with soap and water. If in eyes: flush with large amounts of water for 15 minutes, lifting upper and lower lids occasionally. Get medical attention. If swallowed: Do not induce vomiting, call a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

Caution: VAPOR HARMFUL! Use only in well ventilated areas. Prevent build-up of vapors by opening all windows and doors or use other means to achieve cross-ventilation of moving fresh air across work area at all times. Do not use around sources of ignition such as open flames, pilot lights, etc. Do not smoke. Do not store at temperatures above 120° F, or in direct sunlight. Do not incinerate container. Wrap empty container and put in trash collections. Do not store in Aluminum containers.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com

#011

Non-Flammable Cleaning Solvent

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol USA, LLC
Address: 300 Cross Plains Blvd., Dalton, GA 30720
Telephone #: 1-800-831-8381
Emergency D.O.T. Only: 1-800-535-5053
Generic ID: Cleaning Solvent
DOT Hazard Classification: Trichloroethylene, 6.1, UN1710, PGIII, RQ
Product Identity: #011 Non Flammable Cleaning Solvent
HMIS: H=2 F=1 R=0

SECTION II - HAZARDOUS COMPONENTS

Trichloroethylene: 100.00 % (BY WT.); 100 ppm PEL; 100 ppm TLV (CAS# 79-01-6) SARA Title III Reportable: Trichloroethylene

SECTION III - PHYSICAL DATA

Initial Boiling Point: 188°F. Vapor Pressure: 58 mm Hg @68°F. Vapor Density (Air=1.0): 4.50. Specific Gravity: 1.45. Percent Volatiles: 100.00.

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: None. Explosive Limit (Product): Lower- 8% Upper- 10.5%. Extinguishing Media: CO₂, dry chemical, or foam. Hazardous Decomposition Products: May form toxic materials: carbon dioxide, hydrogen chloride, phosgene, chlorine and carbon monoxide, various hydrocarbons, of unknown structures. Special Fire Fighting Procedures: Water may be used to keep fire-exposed containers cool until fire is out. Wear self contained breathing apparatus with full face-piece operated pressure-demand or other positive pressure mode when fighting fires. Unusual Fire & Explosion Hazards: Never use welding or cutting torch on or near cans (even empty) because resultant pressure could rupture. Empty cans should be incinerated. All five gallon pails and larger metal containers should be grounded and/or bonded when materials are transferred.

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: 100 ppm. Threshold Limit Value: 100 ppm. Effects Of Exposure: Eyes- Can cause severe irritation, redness, tearing, blurred vision. Skin- Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis. Breathing- Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation. First Aid: Skin - Soap and water. Eyes - Flush with water, lifting upper and lower lids occasionally. Ingestion - Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation - If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Use only in well ventilated areas.

SECTION VI - REACTIVITY DATA

Hazardous Polymerization: Cannot occur. Stability: Stable.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material and transfer to hood. Allow volatile portion to evaporate in hood. Allow sufficient time for vapors to completely clear hood duct work. Dispose of remaining material in accordance with applicable regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

Ventilation: Adequate ventilation is essential to prevent vapor buildup. Open all available windows and entrances to insure good ventilation. Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Respirator Protection: Adequate ventilation is normally sufficient. If TLV of the product or any component is exceeded or eyes begin to water or dizziness or headaches are experienced, increase fresh air supply, wear an NIOSH approved respirator, or leave the area. Engineering or administrative controls should be implemented to reduce exposure. Protective Gloves: Wear protective gloves to prevent skin contact. Eye Protection: Wear glasses or protective goggles to avoid slashes. Other Protective Equipment: None required. Wash Hands Thoroughly with Soap and Water.

SECTION IX - SPECIAL PRECAUTIONS

WARNING: IARC has classified Trichloroethylene in Group 2A, as a substance considered "probably" carcinogenic to humans. IARC, following its own restrictive classification scheme, concluded that there is "limited" evidence of carcinogenicity in humans on the basis of a combination of the results of some of the available epidemiological studies. Product is listed under California Proposition 65.

Harmful if inhaled and may cause delayed lung injury. Can cause nervous system depression. Aspiration hazard if swallowed - can enter lungs and cause damage. KEEP OUT OF REACH OF CHILDREN. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact. Keep away from heat, sparks and flames. Aluminum equipment should not be used for storage or transfer. Contact with aluminum parts in a pressurizable fluid system may cause violent reaction. KEEP OUT OF REACH OF CHILDREN

Capitol USA believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com