

MATERIAL SAFETY DATA SHEET

NFPA RATING: Health = 0 Flammability = 0 Reactivity = 0
 HMIS RATING: Health = 0 Flammability = 0 Reactivity = 0

SECTION I - IDENTITY AND MANUFACTURER'S INFORMATION

Manufacturer's Name: HILLYARD INDUSTRIES
 Address: 302 North Fourth Street
 St. Joseph, MO 64501

(0617A)
 Product Name: SEAL 341

Date Prepared: June 7, 1994

Prepared by: Regulatory Affairs Department

Other information calls: (816)233-1321(Ext. 303)

Emergency Telephone No.: (800)-424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.)

SECTION II - INGREDIENTS/IDENTITY INFORMATION

Components

(Specific Chemical Identity:

Common Name(s)

Zinc oxide⁽¹⁾

Water

Acrylic copolymer

Styrene acrylic emulsion

Tributoxyethyl phosphate*

Diethylene glycol monoethyl ether*

Diethylene glycol mono methyl ether* (2)

(1) Regulated by OSHA and the following states: FL., IL., LA., MA., NJ.

(2) Regulated by the following states: FL., PA., RI.

*This product contains the following chemicals subject to the reporting requirements of SARA Title III, Sec. 313, and 40 CFR Part 372: Tributoxyethyl phosphate, Diethylene glycol monoethyl ether and Diethylene glycol mono methyl ether.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: (739 mm Hg.) corr. 198.26°F

Vapor Pressure (mm Hg.): 21.1

Vapor Density (AIR = 1): 1.1

Solubility in Water: appreciable

Specific Gravity (H₂O = 1): 25°C = 1.04 & 39°C = 1.03

Percent Volatile by Volume (%): 77.8

Evaporation Rate (ethyl ether = 1): slower than 1

Appearance and Odor: milky emulsion; non-objectionable odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash point: none (Tag Closed Cup)

Extinguishing Media: N/A

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: Material may spatter if temperature exceeds boiling point. Polymer film can burn.

Flammable Limits: LEL = N/A UEL = N/A

SECTION V - PHYSICAL HAZARDS

Stability: Stable

Incompatibility (Materials to Avoid): None known

Hazardous Decomposition Products or Byproducts:

Hazardous Polymerization: Will not occur

Thermal decomposition may yield acrylic monomers (avoid temperatures above 177°C/350°F). Thermal decomposition is dependent on time and temperature.

Conditions to Avoid: N/A

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? N/A

Skin? N/A

Ingestion? N/A

HEALTH HAZARDS (1. Acute and 2. Chronic)

1. Mild eye irritation.

2. None known.

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No

I.A.R.C. Monographs = No

OSHA = No

This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater or equal to 0.1%.

SECTION VI - HEALTH HAZARD DATA cont.

Signs and Symptoms of Exposure: None known.

Medical Conditions Generally Aggravated by Exposure: None known.

Emergency and First Aid Procedures: If splashed into eyes flush with water for 15 minutes; if irritation persists get medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Pick up with mop or wet vac and wash away with water. Ventilate area of spill or leak. Transfer liquids and diking material to separate suitable containers for recovery or disposal. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Method: Spills should be picked up with wet vac or absorbent material. Dispose of liquid per federal, state and local regulations. Waste from normal product use may be sewerred to a public owned treatment works (POTW) in compliance with applicable federal, state and local requirements.

Precautions To Be Taken In Handling And Storing: Freezing of product may rupture container. Product shelf life is best retained by storage at 45-100 °F temperatures.

Other Precautions: Inhalation exposure to spray mist should be maintained at less than 10 mg/M³ per eight hour exposure (TWA limit est. for nuisance dust).

SECTION VIII - CONTROL MEASURES:

Respiratory Protection (Specify Type): When airborne exposure guidelines and/or comfort levels may be exceeded, use an approved air-purifying respirator.

Ventilation:

Local Exhaust = Not required

Mechanical (General) = Suggested

Special = N/A **Other =** 1

Protective Gloves: None required for brief contact **Eye Protection:** Chemical goggles (contact may cause pain, though it is unlikely to cause injury).

Other Protective Clothing or Equipment: Use good personal hygiene procedures.

Work/Hygienic Practices: Do not take internally; wash contaminated clothing before reuse.

SECTION IX - TRANSPORTATION INFORMATION:

Applicable regulations: 49 CFR = no; IMCO = no; IATA = no.

Proper shipping name: Liquid Floor Wax & Polish

UN No.: not applicable; **Limited Qty.:** not applicable; **Hazard Class:** not applicable.

Labels required: not required **DOT Exception:** not applicable

EPA Hazardous waste number / code: not listed

Hazardous waste characteristics: not applicable

Ignitability = not applicable; **Corrosivity =** not applicable; **Reactivity =** not applicable.

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.