

AP GREEN INDUSTRIES INC -- INSULATING CEMENT

MSDS Safety Information

FSC: 5610
MSDS Date: 05/25/1994
MSDS Num: CBCSX
LIIN: 00N065273
Product ID: INSULATING CEMENT
MFN: 01
Responsible Party
Cage: IO143
Name: AP GREEN INDUSTRIES INC
Address: GREEN BLVD
City: MEXICO MO 65265
Info Phone Number: 314-473-3626
Emergency Phone Number: 314-473-3626
Proprietary Ind: Y
Published: Y

Contractor Summary

Cage: IO143
Name: AP GREEN INDUSTRIES INC
Address: GREEN BLVD
City: MEXICO MO 65265
Phone: 314-473-3392
Cage: 84446
Name: GREEN A.P. INDUSTRIES INC
Address: GREEN BLVD
City: MEXICO MO 65265-2582
Phone: 314-473-3355

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: YES
IARC: YES
OSHA: NO
Effects of Exposure: ACUTE: EYES: CAUSES IRRITATION. SKIN: MAY CAUSE SKIN IRRITATION. INHALATION: MAY CAUSE RESPIRATORY IRRITATION. INGESTION: CONSULT MD IMMEDIATELY. CHRONIC: PROLONGED IRRITATION OF MINERAL WOOL DUST MAY REDUCE LUNG FUNCTION. PROLONGED EXPOSURE TO DUST MAY CAUSE SILICOSIS, A PROGRESSIVE PNEUMOCONIOSIS (EFTS OF OVEREXP)
Explanation Of Carcinogenicity: SEE "LR" VERSION, ING 6, FOR ADDITIONAL INFORMATION (FP N).
Signs And Symptions Of Overexposure: HLTH HAZ: OR OTHER RESPIRATORY DISEASES. IARC CONTINUES TO CLASSIFY MINERAL WOOL FIBER IN CATEGORY OF 2B (MFR).
Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.
First Aid: EYES: IMMEDIATELY RINSE EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES UNTIL IRRITATION STOPS. SKIN: WASH FREQUENTLY WITH SOAP AND WATER TO MINIMIZE IRRITATION. INHAL: REMOVE TO FRESH AIR. REMOVE F IBERS AND DUST FROM NOSE AND DRINK WATER TO CLEAR THROAT. INGEST: CONSULT MD IMMEDIATELY. NOTE: SHOULD ANY OF THE ABOVE CONDITIONS PERSIST, CONSULT MD.

Handling and Disposal

Spill Release Procedures: AVOID CREATING DUST. USE VACUUM OR WET CLEAN-UP TO MINIMIZE DUST.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: MINERAL WOOL FIBER PRODUCTS ARE GENERALLY CLASSIFIED AS A NON-HAZARDOUS WASTE AND MAY BE DISPOSED OF IN A NONCRITICAL LANDFILL. ALWAYS CHECK ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: NIOSH/MSHA APPRVD RESPS SHOULD BE WORN ANYTIME REFRACTORIES ARE TORN OUT AFTER SERVICE. WHILE SOME RESP HAZS &/OR NUISANCE DUST MAY EXIST (SUPDAT)

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: NON-COMBUSTIBLE

Extinguishing Media: MATERIAL COMPATIBLE WITH CARBON DIOXIDE, WATER OR DRY CHEMICAL EXTINGUISHING MEDIA.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: NONE.

=====

Control Measures

=====

Respiratory Protection: WEAR NIOSH/MSHA APPROVED RESPIRATORS.

Ventilation: USE SUFFICIENT VENT (NATRL OR MECH) WHILE HNDLG THIS MATL IN DRY STATE TO MAINTAIN AIRBORNE DUST LEVELS BELOW TLV.

Protective Gloves: WATERPROOF OR RUBBER GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER (FP N). LONG SLEEVED, LOOSE FITTING CLOTHING & CAP SHOULD BE WORN.

Work Hygienic Practices: WASH ALL WORK CLTHG SEPARATE FROM OTHER CLTHG TO PREVENT POSSIBLE MIGRATION OF MINERAL WOOL FIBER & DUST TO OTHER CLTHG.

Supplemental Safety and Health: USERS OF "L" VERSION SHOULD CONSULT "LR" VERSION FOR ADDITIONAL INFO (FP N). HNDLG/STOR PRECS: FROM PRODUCT ITSELF, OTHER FOREIGN SUBSTANCES MAY WARRANT ADDITIONAL PRECAUTIONS DURING TEAR OUT & DISPOS AL.

=====

Physical/Chemical Properties

=====

Appearance and Odor: DRY, GRANULAR MIXTURE, GRAY IN COLOR; NO ODOR.

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: STRONG ACIDS.

Hazardous Decomposition Products: NONE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

HAZCOM Label

=====

AP GREEN INDUSTRIES INC -- INSULATING CEMENT

MSDS Safety Information

FSC: 5610
MSDS Date: 05/25/1994
MSDS Num: CBCSX
LIIN: 00N065273
Product ID: INSULATING CEMENT
MFN: 01
Responsible Party
Cage: IO143
Name: AP GREEN INDUSTRIES INC
Address: GREEN BLVD
City: MEXICO MO 65265
Info Phone Number: 314-473-3626
Emergency Phone Number: 314-473-3626
Proprietary Ind: Y
Published: Y

Contractor Summary

Cage: IO143
Name: AP GREEN INDUSTRIES INC
Address: GREEN BLVD
City: MEXICO MO 65265
Phone: 314-473-3392
Cage: 84446
Name: GREEN A.P. INDUSTRIES INC
Address: GREEN BLVD
City: MEXICO MO 65265-2582
Phone: 314-473-3355

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: YES
IARC: YES
OSHA: NO
Effects of Exposure: ACUTE: EYES: CAUSES IRRITATION. SKIN: MAY CAUSE SKIN IRRITATION. INHALATION: MAY CAUSE RESPIRATORY IRRITATION. INGESTION: CONSULT MD IMMEDIATELY. CHRONIC: PROLONGED IRRITATION OF MINERAL WOOL DUST MAY REDUCE LUNG FUNCTION. PROLONGED EXPOSURE TO DUST MAY CAUSE SILICOSIS, A PROGRESSIVE PNEUMOCONIOSIS (EFTS OF OVEREXP)
Explanation Of Carcinogenicity: SEE "LR" VERSION, ING 6, FOR ADDITIONAL INFORMATION (FP N).
Signs And Symptions Of Overexposure: HLTH HAZ: OR OTHER RESPIRATORY DISEASES. IARC CONTINUES TO CLASSIFY MINERAL WOOL FIBER IN CATEGORY OF 2B (MFR).
Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.
First Aid: EYES: IMMEDIATELY RINSE EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES UNTIL IRRITATION STOPS. SKIN: WASH FREQUENTLY WITH SOAP AND WATER TO MINIMIZE IRRITATION. INHAL: REMOVE TO FRESH AIR. REMOVE F IBERS AND DUST FROM NOSE AND DRINK WATER TO CLEAR THROAT. INGEST: CONSULT MD IMMEDIATELY. NOTE: SHOULD ANY OF THE ABOVE CONDITIONS PERSIST, CONSULT MD.

Handling and Disposal

Spill Release Procedures: AVOID CREATING DUST. USE VACUUM OR WET CLEAN-UP TO MINIMIZE DUST.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: MINERAL WOOL FIBER PRODUCTS ARE GENERALLY CLASSIFIED AS A NON-HAZARDOUS WASTE AND MAY BE DISPOSED OF IN A NONCRITICAL LANDFILL. ALWAYS CHECK ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: NIOSH/MSHA APPRVD RESPS SHOULD BE WORN ANYTIME REFRACTORIES ARE TORN OUT AFTER SERVICE. WHILE SOME RESP HAZS &/OR NUISANCE DUST MAY EXIST (SUPDAT)

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====

Fire and Explosion Hazard Information

=====

Flash Point Text: NON-COMBUSTIBLE

Extinguishing Media: MATERIAL COMPATIBLE WITH CARBON DIOXIDE, WATER OR DRY CHEMICAL EXTINGUISHING MEDIA.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: NONE.

=====

Control Measures

=====

Respiratory Protection: WEAR NIOSH/MSHA APPROVED RESPIRATORS.

Ventilation: USE SUFFICIENT VENT (NATRL OR MECH) WHILE HNDLG THIS MATL IN DRY STATE TO MAINTAIN AIRBORNE DUST LEVELS BELOW TLV.

Protective Gloves: WATERPROOF OR RUBBER GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER (FP N). LONG SLEEVED, LOOSE FITTING CLOTHING & CAP SHOULD BE WORN.

Work Hygienic Practices: WASH ALL WORK CLTHG SEPARATE FROM OTHER CLTHG TO PREVENT POSSIBLE MIGRATION OF MINERAL WOOL FIBER & DUST TO OTHER CLTHG.

Supplemental Safety and Health: USERS OF "L" VERSION SHOULD CONSULT "LR" VERSION FOR ADDITIONAL INFO (FP N). HNDLG/STOR PRECS: FROM PRODUCT ITSELF, OTHER FOREIGN SUBSTANCES MAY WARRANT ADDITIONAL PRECAUTIONS DURING TEAR OUT & DISPOSAL.

=====

Physical/Chemical Properties

=====

Appearance and Odor: DRY, GRANULAR MIXTURE, GRAY IN COLOR; NO ODOR.

=====

Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: STRONG ACIDS.

Hazardous Decomposition Products: NONE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

HAZCOM Label

=====

=====

Product ID: INSULATING CEMENT
Cage: IO143
Assigned IND: Y
Company Name: AP GREEN INDUSTRIES INC
Street: GREEN BLVD
City: MEXICO MO
Zipcode: 65265
Health Emergency Phone: 314-473-3626
Label Required IND: Y
Date Of Label Review: 11/14/1995
Status Code: C
Label Date: 11/14/1995
Origination Code: G
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: None
Reactivity Hazard: None
Hazard And Precautions: ACUTE: MAY CAUSE EYE, SKIN OR RESPIRATORY IRRITATION.
CHRONIC: CANCER HAZARD. CONTAINS MATERIAL WHICH IS LISTED AS AN ANIMAL LUNG
CARCINOGEN (FP N). PROLONGED INHALATION MAY REDUCE LUNG FUNCTION. DUST MAY
CAUSE SILICOSIS OR OTHER RESPIRATORY DISEASES.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.

