

6289



Material Safety Data Sheet

Contractor's Choice Multi-Purpose Adhesive

Complies with OSHA's Hazard Communication Standard CFR 1910.1200

Material Identity

HMIS: H: 1 / F: 3 / R: 1 / P: G

Product Code and Name: Contractor's Choice Multi-Purpose Adhesive

Product Class: Solvent-Based Adhesive

DOT Class: 1 Gallon or larger: Adhesives, Flammable Liquid, UN 1133, Packing Group 3

Less than 1 gallon: Consumer Commodity ORM-D

NFPA Class III B

Manufacturer: Macklanburg-Duncan
4041 North Santa Fe
Oklahoma City, OK 73118
1(800)654-8454

24 Hour Emergency: Chemtrec 1(800)424-9300

Date Prepared: September 30, 1999

Replaces: July 14, 1999

Component	OSHA PEL	ACGIH TLV	%	CAS Number
Petroleum Distillates	** 100 ppm TWA	** 100 ppm TWA	< 35	64742-49-0
* 5 Toluene	200 ppm	50 ppm	< 6	108-88-3

5 This product contains a chemical known to the State of California to cause developmental toxicity.

* This product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right To Know Act of 1986 (40CFR 372).

** Based on a similar product.

Physical Properties

Vapor Density (air = 1):	Not determined	Boiling Point:	Not determined
Specific Gravity:	Not determined	Percent Volatile by Volume:	Not determined
Solubility in Water:	Insoluble	Vapor Pressure (mm Hg):	Not determined
Evaporation Rate (ether = 1):	Not determined	Appearance and odor:	Light brown/green mastic, sweet odor
% Solids:	64%	V.O.C.:	384 g/L

Fire and Explosion Hazards

Flash Point (Seta Flash CC):	0°F, wet	Flammable Limits:	Not determined
Extinguishing Media:	Carbon dioxide, foam, dry chemical (Class 1B fire extinguishers)		
Special Fire Fighting Procedures:	WARNING! EXTREMELY FLAMMABLE. Wear self-contained breathing apparatus in positive pressure mode and full protective gear.		
Unusual Fire and Explosion Hazards:	Irritating or toxic gases and aerosols may be produced during burning. Vapors may ignite explosively and may travel along the ground or be moved by ventilation and ignited by static electricity, motors, flames, etc.		

Stability: Stable

Conditions to Avoid: Heat, sparks, flame, ignition sources



Material Safety Data Sheet

Contractor's Choice Multi-Purpose Adhesive

Incompatibility (Materials to Avoid): Oxidizing agents

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, aromatic and aliphatic hydrocarbons

Hazardous Polymerization: None

Effects of Exposure and First Aid Procedures:

Inhalation: May cause respiratory irritation, dizziness, weakness, fatigue and nausea. Avoid breathing vapors. **Skin:** May cause irritation. In case of contact, wash affected area with soap and water. **Eyes:** Eye contact may cause blurred vision, or irritation. If contact occurs, flush with water for 15 minutes and contact physician. **Ingestion:** Do not ingest. If ingested, do not induce vomiting. Contact physician. If vomiting occurs, keep head below hips to prevent aspiration of liquid.

Carcinogenicity: IARC: 3 (Toluene)

Steps to be taken in case material is spilled or released:

Apply ventilation. Extinguish sources of spark or flame. Add sand or other absorbent material to spill area. Pick up with non-metallic material. Scrape into containers and dispose of in accordance with local, state, and federal regulations.

Waste disposal method:

Place in a disposal facility approved under RCRA regulations for hazardous waste. May be incinerated following approved regulations.

Handling and Storage Precautions:

WARNING! EXTREMELY FLAMMABLE. Do not store near heat sources, sparks or flame. Store between 40°F and 100°F. If storing outside, protect from sun to avoid overheating of containers. When puncturing seal, turn container away from face and body.

Transportation Data:

1 Gallon or larger: Adhesives, Flammable Liquid, UN 1133, Packing Group 3
Less than 1 gallon: Consumer Commodity ORM-D DOT E-150 NFPA Class IIIB

Other Precautions:

WARNING! EXTREMELY FLAMMABLE. Keep away from heat, sparks, flame, or sources of ignition. Do not smoke when using this product. Do not ingest. Store in a cool location. Avoid breathing vapors. **KEEP AWAY FROM CHILDREN.**

Respiratory Protection: Use NIOSH approved vapor cartridge respirator if vapors exceed TLV.

Ventilation: Use only in well-ventilated area. Use adequate ventilation to keep vapors below TLV.

Protective Gloves: Nitrile

Eye Protection: Normal precaution

Hygienic Practices: Wash skin and hands after use. Do not smoke when using this product.

Disclaimer: This Safety Data Sheet was prepared to protect against any reasonable exposure to consumers or employees arising out of the intended use of the product and to provide them with information regarding potential hazards contained in the product. Under varied circumstances the hazardous ingredients may pose a lesser or greater hazard. Because of the scientific data contained in these sheets was obtained from tests performed by agencies other than Macklanburg-Duncan Company, the company cannot guarantee its accuracy. Macklanburg-Duncan Company makes no warranty of any kind, expressed or implied. The user must assume all risk and liability resulting from reliance on the information contained on this Material Safety Data Sheet and the use of this product, whether used in combination with other products or singly.