

MATERIAL SAFETY DATA SHEET

20009TF
 CC

MANUFACTURER'S NAME
 THE SHERWIN-WILLIAMS COMPANY
 Diversified Brands
 Cleveland, OH 44115

EMERGENCY TELEPHONE NO.
 (216) 566-2917

DATE OF PREPARATION
 11-MAY-00

INFORMATION TELEPHONE NO.
 (800) 632-2344

Section I -- PRODUCT IDENTIFICATION

PRODUCT NUMBER

20009TF

HMIS CODES
 Health 2
 Flammability 4
 Reactivity 0

PRODUCT NAME

20009TF LUBRICANT 40Z

Lubricant

PRODUCT CLASS

Acrosol Lubricant

Section II -- HAZARDOUS INGREDIENTS

INGREDIENT CAS. No.	% BY WT	ACGIH TLV	OSHA PEL	UNITS	V.P.
Propane 74-98-6	10	2500	1000	PPM	760.00
BUTANE 106-97-8	10	800	800	PPM	760.00
Heavy Aliphatic Solvent 64742-96-7	24	Not Established			1.00
Naphthenic Oil. 64742-63-8	18	5	MG/M3 as M		0.00
Heavy Naphthenic Petroleum Oil. 64742-52-5	2	5	5 MG/M3 as M		0.00
Highly refined Naphthenic Oil. 64742-53-6	3	5	5 MG/M3 as M		0.00
Heavy Mineral Oil. 64741-96-4	10	5	5 MG/M3 as M		0.10
Distillates, petroleum, solvent ds 64742-65-0	2	5	5 MG/M3 as M		0.00
2-Methoxy-2-methylpropanol 34190-94-4	2 STBL	100 150	100 PPM (Skin) 150 PPM (Skin)		0.40
Amyl Acetate 628-63-7	2	100	100 PPM		4.00
Barium (as Ba; total)		0.69			

Continued on page 2

Facsimile Fax Note	7671	Date	5/11/00	Page	4
To	DLV	From	DLV		
Company	LS BULL	Co.			
Phone #		Phone #			
Fax #	986-3345	Fax #			

Section III - PHYSICAL DATA

PRODUCT WEIGHT 6.46 lb/gal 774 g/l
SPECIFIC GRAVITY 0.78
BOILING POINT <0 - 701 F <-18 - 371 C
MELTING POINT Not Available
VOLATILE VOLUME 56 %
EVAPORATION RATE Faster than ether
VAPOR DENSITY Heavier than air
SOLUBILITY IN WATER N.A.
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)
Volatile Weight 48.20 % Less Federally Exempt Solvents
HMIS -- 2 4 0

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT LEL UEL
40 F TCC 0.6 9.5
EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build up and possible autoignition or explosion when exposed to extreme heat.

Section V -- HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards**EFFECTS OF OVEREXPOSURE**

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

Continued on page 3

EMERGENCY AND FIRST AID PROCEDURES

- If INHALED: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.
- If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
- If in EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.
- If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.
Reports have associated repeated and prolonged overexposure to solvents
with permanent brain and nervous system damage.

Section VI -- REACTIVITY DATA

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide, Oxides of Metals in Section II

HAZARDOUS POLYMERIZATION

Will not occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert
sorber.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource
Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability and extractability to determine
the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance
with Federal, State, and Local regulations regarding pollution.

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray
mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to
materials in Section II is maintained below applicable exposure limits.
Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by
ventilation, wear a properly fitted organic vapor/particulate respirator
approved by NIOSH/MSHA for protection against materials in Section II.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal
skin contact is expected. For long or repeated contact, wear chemical
resistant gloves.

Continued on page 4

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section IX -- PRECAUTIONS

DOL STORAGE CATEGORY

1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and open flame.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section X -- OTHER REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
	Barium Compound.	3	0.7

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.