

MATERIAL SAFETY DATA SHEET

Quick Identifier (In Plant Common Name): PerfectData EcoDuster II

MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: SPRAY PRODUCTS CORPORATION
ADDRESS: P.O. Box 737, Norristown, PA 19404
EMERGENCY TELEPHONE NUMBER: Chemtrec 1-800- 424-9300
GENERAL INFORMATION TELEPHONE NUMBER: 1-610-277-1010
DATE PREPARED: March 11, 2008

SECTION 1 - IDENTITY

COMMON NAME (used on label)(Trade Name & Synonyms): PerfectData Eco Duster II 10 oz 105842-1
CAS. NUMBER: See Section 2
CHEMICAL NAME: 1,1-Difluoroethane
CHEMICAL FAMILY: N/A
FORMULA: n/a

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s)

CHEMICAL AND COMMON NAME(S)	CAS. #	TLV	ACGIH	VAPOR PRESSURE @ 25 DEG. C	LEL	UEL	FLASH POINT DEG. F
1,1 Difluoroethane	75-37-6	1000ppm	1000ppm	62 psig	3.9	16.9	-58

*Limit established by The E.I. DuPont Company is 1000ppm

N/A is not available or not applicable

NOTE: This product does not contain any ingredients subject to Section 313 of SARA Title III.

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

BOILING POINT (Deg. F): -13

SPECIFIC GRAVITY (Water = 1): 1.00

VAPOR PRESSURE (mmHg): See Section 2

PERCENT VOLATILE BY WEIGHT (%): 100%

VAPOR DENSITY (Air = 1): >1

EVAPORATION RATE (BA = 1): >1

SOLUBILITY IN WATER: Substantial

REACTIVITY IN WATER: None

APPEARANCE AND ODOR: Clear gas at standard temperature and pressure with a slight ethereal odor; **FINISHED PACKAGE:** Aerosol container filled with liquefied gas.

FLASH POINT: See Section 2

FLAMMABLE LIMITS IN AIR - % BY VOLUME: See Section 2

EXTINGUISHER MEDIA: Dry chemical, carbon dioxide, foam

AUTO-IGNITION TEMPERATURE: Unknown

SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure build-up and possible bursting when exposed to high temperatures. Firemen should wear self-contained, positive pressure, respiratory equipment. Hazardous decomposition products.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Although aerosols are classified as nonflammable by 16CFR1500.3(c)(6) of the Federal Hazardous Substance Act, C.P.S.C. Regs, this product does contain flammable ingredients and therefore should not be used or stored near any open flames or ignition sources. Contents under pressure. Keep temperature of containers below 120 deg. F. to prevent bursting. Exposure to temperature above 120 deg. F. may cause can to burst with violence and cause injury.

SECTION 4 - PHYSICAL HAZARDS

STABILITY: Stable

CONDITIONS TO AVOID: Avoid any excessive heat, ignition sources, open flames, or other high temperatures which induce thermal decomposition.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizers. Alkali or alkaline earth metals - powdered Aluminum, Zinc, Be, etc.

HAZARDOUS DECOMPOSITION PRODUCTS: This material can be decomposed by high temperature (open flames, flowing metal surfaces, etc.) forming hydrofluoric acids and possibly carbonyl halides. Carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Not Applicable

SECTION 5 - HEALTH HAZARDS

THRESHOLD LIMIT VALUE: See Section 2

SIGNS AND SYMPTOMS OF EXPOSURE: **EYE CONTACT:** Liquid contact can cause frostbite; **SKIN CONTACT:** Liquid contact can cause frostbite; **INHALATION:** Vapor is heavier than air and can cause suffocation by reducing oxygen available for breathing. Breathing high concentrations of vapor may cause lightheadedness, giddiness, shortness of breath, and may lead to narcosis, cardiac irregularities, unconsciousness or death. *INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS OF THE CAN MAY BE HARMFUL OR FATAL.*

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN:

NATIONAL TOXICOLOGY PROGRAM: No

I.A.R.C. MONOGRAPHS: No

OSHA: No

OSHA PERMISSIBLE EXPOSURE LIMIT: See Section 2

AGCIH THRESHOLD LIMIT VALUE: See Section 2

OTHER EXPOSURE LIMITED USED: None

EMERGENCY AND FIRST AID PROCEDURE

INHALATION: If high concentrations are inhaled: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Do not give epinephrine or similar drugs. Call a physician. **EYES:** In case of eye contact, immediately flush eyes with plenty of cold water. Call a physician. **SKIN:** In case of skin contact, flush with water. Treat for frostbite if necessary. **INGESTION:** Ingestion is not considered a potential route of exposure.

NOTE TO PHYSICIANS: *BECAUSE OF POSSIBLE DISTURBANCES OF CARDIAC RHYTHM, CATECHOLAMINE DRUGS, SUCH AS EPINEPHRINE, SHOULD ONLY BE USED WITH SPECIAL CAUTION IN SITUATIONS OF EMERGENCY LIFE SUPPORT.*

SECTION 6 - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Under normal use conditions, no respiratory protection is required. Self-contained breathing apparatus (SCBA) is required if a large spill or release occurs.

VENTILATION:

LOCAL EXHAUST: To keep below TLV

MECHANICAL (General): To keep below TLV

SPECIAL: None

OTHER: None

PROTECTIVE GLOVES: Lined butyl gloves should be worn when handling liquid.

EYE PROTECTION: Safety glasses or goggles should be worn when handling liquid.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None reasonably foreseeable.

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Liquid contents may cause frostbite on contact with skin; therefore, do not tilt, shake, or turn can upside down before or during use. Do not store above 110 Deg. F. Do not use or store near any open flames or ignition sources.

OTHER PRECAUTIONS: Contents under pressure. Do not puncture or incinerate. Exposure to temperatures above 120 Deg. F may cause can to burst with violence and cause injury. Vapors are heavier than air and will collect in low areas.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area - especially low places where heavy vapors might collect. Remove open flames. Use self-contained breathing apparatus for large spills.

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State, and Local regulations. Do not incinerate closed or empty containers.

SECTION 8 - NFPA HAZARD RATINGS

Health = 1 Flammability = 4 Reactivity = 0

Section 9 - Other Information

TRANSPORTATION INFORMATION - DOMESTIC GROUND

Shipping Name: 1,1-Difluoroethane

Hazard Class: 2.1

UN Number: UN1030

Packing Group: N/A

Hazard Label: Not required for domestic ground shipping per DOT-SP 11516

Carton Marking: 1,1-Difluoroethane, 2.1, UN1030. Inside Containers comply with DOT-SP 11516

A current copy of DOT-SP 11516 must be maintained at each facility where the package is offered or reoffered for transportation.

NOTE: For domestic shipments, outer boxes must be marked with designation DOT-E11516 as well as shipping name, hazard class (2.1) and UN number. Domestic shipments are exempt from labeling and

shipping paper requirements except when transported by air.

TRANSPORTATION INFORMATION – DOMESTIC AIR

Shipping Name:	1,1-Difluoroethane
Hazard Class:	2.1
UN Number:	UN1030
Packing Group:	N/A
Hazard Label:	Flammable Gas, Cargo Aircraft Only
Carton Marking:	1,1-Difluoroethane, 2.1, UN1030. Inside Containers comply with DOT-SP 11516

A copy of DOT-SP 11516 must be carried aboard each aircraft used to transport this product.

Disclaimer

SPRAY PRODUCTS CORPORATION believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability, or completeness of the information. Persons receiving this information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY SPRAY PRODUCTS CORPORATION.