

MATERIAL SAFETY DATA SHEET

EQUILON MSDS: 71630E-12 01/04/99

ROTELLA(R) T 15W-40 WITH ADVANCED SOOT CONTROL



TELEPHONE NUMBER: 24 HOUR EMERGENCY ASSISTANCE
 EQUIVA SERVICES: 877-276-7283
 CHEMTREC: 800-424-9300

NAME AND ADDRESS
 EQUILON ENTERPRISES LLC
 PRODUCT STEWARDSHIP
 P.O. BOX 674414
 HOUSTON, TX 77267-4414

GENERAL MSDS ASSISTANCE
 877-276-7283

SECTION I NAME

PRODUCT: ROTELLA(R) T 15W-40 WITH ADVANCED SOOT CONTROL
 CHEM NAME: MIXTURE (SEE SECTION II-A)
 CHEM FAMILY: PETROLEUM HYDROCARBON; MOTOR OIL
 SHELL CODE: 50012
 HEALTH HAZARD: 1 FIRE HAZARD: 1 REACTIVITY: 0

SECTION II-A PRODUCT/INGREDIENT

NO.	COMPOSITION	CAS NO.	PERCENT
1	ROTELLA T 15W-40 WITH ADVANCED SOOT CONTROL		100
2	ADDITIONS CONTAINING:		
2A	ZINC COMPOUND		
1	HIGHLY REFINED PETROLEUM OIL		70-80
2	MIXTURE		20-30
1-2	MIXTURE		1-2

SECTION II-B ACUTE TOXICITY DATA

NO.	ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
1	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE
1	>5.0 G/KG (RAT) *	>5.0 G/KG (RABBIT) *	NOT AVAILABLE

* BASED ON API STUDIES

SECTION III

HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

EYE CONTACT: LUBRICATING OILS ARE GENERALLY CONSIDERED NO MORE THAN MINIMALLY IRRITATING TO THE EYES.

SKIN CONTACT: LUBRICATING OILS ARE GENERALLY CONSIDERED NO MORE THAN MILDLY IRRITATING TO THE SKIN. PROLONGED AND REPEATED CONTACT MAY RESULT IN VARIOUS SKIN DISORDERS SUCH AS DERMATITIS, FOLLICULITIS OR OIL ACNE.

INHALATION: INHALATION OF VAPOR (GENERATED AT HIGH TEMPERATURES ONLY) OR OIL MIST FROM THIS PRODUCT MAY RESULT IN MILD IRRITATION OF THE UPPER RESPIRATORY TRACT.

INGESTION: LUBRICATING OILS ARE GENERALLY CONSIDERED NO MORE THAN SLIGHTLY TOXIC IF SWALLOWED.

SIGNS AND SYMPTOMS: IRRITATION AS NOTED ABOVE.

AGGRAVATED MEDICAL CONDITIONS: PREEXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS:

THIS PRODUCT AND ITS COMPONENTS ARE NOT CLASSIFIED AS CARCINOGENS BY THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC), NATIONAL TOXICOLOGY PROGRAM (NTP) OR OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA). SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY IN EXPERIMENTAL ANIMALS OF USED MOTOR OILS. HANDLING PROCEDURES AND SAFETY PRECAUTIONS IN THE MSDS SHOULD BE FOLLOWED TO MINIMIZE EMPLOYEE'S EXPOSURE TO THE USED PRODUCT.

FOR A SPANISH TRANSLATION OF THIS MSDS, CALL 1-800-240-MSDS.

SECTION IV

OCCUPATIONAL EXPOSURE LIMITS

COMP	OSHA	PEL/CEILING	TLV/TWA	ACGIH	TLV/STEL	OTHER
NO. PEL/TWA	-----	-----	-----	-----	-----	-----
P 5 MG/M3*	NONE	5 MG/M3*	10 MG/M3*			
*OIL MIST, MINERAL						

SECTION V
EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING AND Wipe EXCESS OFF. WASH WITH SOAP AND WATER OR A WATERLESS HAND CLEANER FOLLOWED BY SOAP AND WATER.

IF IRRITATION OCCURS, GET MEDICAL ATTENTION.
REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS
DIFFICULT. GET MEDICAL ATTENTION.
INGESTION: DO NOT INDUCE VOMITING. IN GENERAL NO TREATMENT IS NECESSARY
UNLESS LARGE QUANTITIES OF PRODUCT ARE INGESTED. HOWEVER, GET
MEDICAL ATTENTION.
NOTE TO PHYSICIAN: IN GENERAL, EMBESIS INDUCTION IS UNNECESSARY IN HIGH
VISCOSITY, LOW VOLATILITY PRODUCTS, I.E., MOST OILS AND
GREASES.

SECTION VI SUPPLEMENTAL HEALTH INFORMATION

NONE IDENTIFIED.

SECTION VII PHYSICAL DATA

BOILING POINT (DEG F): NOT AVAILABLE
SPECIFIC GRAVITY (H₂O = 1): 0.8644
VAPOR PRESSURE (MM HG): <0.1
MELTING POINT (DEG F): -25 (FOUR POINT)
SOLUBILITY IN WATER: NEGLECTIBLE
VAPOR DENSITY (AIR = 1): NOT AVAILABLE

VISCOSITY: 13-15 (CS @ 212 DEG F)
EVAPORATION RATE (NORMAL BUTYL ACETATE = 1): NOT AVAILABLE
APPEARANCE AND ODOR: DARK AMBER OIL. SLIGHT HYDROCARBON ODOR.
PHYS/CHEM PROPERTIES: SEE ABOVE FOR DETAILS

SECTION VIII FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD: 380 DEG F (PMCC)
FLAMMABLE LIMITS/PERCENT VOLUME IN AIR: LOWER: N/AV HIGHER: N/AV
EXTINGUISHING MEDIA:

SPILL OR LEAK PROCEDURES:
MAY BURN ALTHOUGH NO READILY IGNITABLE. USE CAUTIOUS JUDGMENT WHEN CLEANING UP LARGE SPILLS. *** LARGE SPILLS *** WEAR RESPIRATOR AND PROTECTIVE CLOTHING AS APPROPRIATE. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND, OR OTHER SUITABLE MATERIALS;

SECTION XI ENVIRONMENTAL PROTECTION

ADDITIONAL PROTECTIVE MEASURES:
NONE IDENTIFIED

PROTECTIVE CLOTHING
WEAR CHEMICAL RESISTANT GLOVES AND OTHER PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE SKIN CONTACT. WEAR SAFETY GOGGLES TO AVOID EYE CONTACT. TEST DATA FROM PUBLISHED LITERATURE AND/OR GLOVE AND CLOTHING MANUFACTURERS INDICATE THE BEST PROTECTION IS PROVIDED BY NITRILE GLOVES.

RESPIRATORY PROTECTION:
IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SECTION IV) USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES.

SECTION X EMPLOYEE PROTECTION

HAZARDOUS DECOMPOSITION PRODUCTS:
THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT ON THE COMBUSTION CONDITIONS. A COMPLEX MIXTURE OF AIRBORNE SOLID, LIQUID, PARTICULATES AND GASES WILL EVOLVE WHEN THIS MATERIAL UNDERGOES PYROLYSIS OR COMBUSTION. CARBON MONOXIDE, HYDROGEN SULFIDE, AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED UPON COMBUSTION.

CONDITIONS AND MATERIALS TO AVOID:
AVOID HEAT, OPEN FLAMES AND OXIDIZING MATERIALS.

STABILITY: STABLE
HAZARDOUS POLYMERIZATION WILL NOT OCCUR

SECTION IX REACTIVITY

UNUSUAL FIRE AND EXPLOSION HAZARDS:
NONE IDENTIFIED

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:
MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONTAINED FIRE-SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE-PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

USE WATER FOG, FOAM, DRY CHEMICAL OR CO₂. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

DISPOSE OF PROPERLY. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. ***
SMALL SPILLS *** TAKE UP WITH AN ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

SECTION XII

SPECIAL PRECAUTIONS

MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING,
SMOKING OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE
REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES, INCLUDING SHOES,
THAT CANNOT BE DECONTAMINATED.
STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN
FLAMES AND HIGH TEMPERATURES.

SECTION XIII

TRANSPORTATION REQUIREMENTS

DEPARTMENT OF TRANSPORTATION CLASSIFICATION:
NOT HAZARDOUS BY D.O.T. REGULATIONS

DOT PROPER SHIPPING NAME: NOT APPLICABLE

OTHER REQUIREMENTS: NOT APPLICABLE

SECTION XIV

OTHER REGULATORY CONTROLS

THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL
SUBSTANCES.

PROTECTION OF STRATOSPHERIC OZONE (PURSUANT TO SECTION 611 OF THE CLEAN AIR ACT
AMENDMENTS OF 1990): PER 40 CFR PART 82, THIS PRODUCT DOES NOT CONTAIN NOR WAS
IT DIRECTLY MANUFACTURED WITH ANY CLASS I OR CLASS II OZONE DEPLETING
SUBSTANCES.

IN ACCORDANCE WITH SARA TITLE III, SECTION 313, THE ATTACHED ENVIRONMENTAL DATA
SHEET (EDS) SHOULD ALWAYS BE COPIED AND SENT WITH THE MSDS.

SECTION XV

STATE REGULATORY INFORMATION

THE FOLLOWING CHEMICALS ARE SPECIFICALLY LISTED BY INDIVIDUAL STATES; OTHER PROD
UCT SPECIFIC HEALTH AND SAFETY DATA IN OTHER SECTIONS OF THE MSDS MAY ALSO BE AP
PLICABLE FOR STATE REQUIREMENTS. FOR DETAILS ON YOUR REGULATORY REQUIREMENTS YO
U SHOULD CONTACT THE APPROPRIATE AGENCY IN YOUR STATE.

Amesbury

page

NAME AND ADDRESS
EQUILON ENTERPRISES
PRODUCT STEWARDSHIP
P.O. BOX 674414
HOUSTON, TX 77267-4414

TELEPHONE NUMBER:
24 HOUR EMERGENCY ASSISTANCE
EQUIVA SERVICES: 877-276-7283
CHEMTREC: 800-424-9300
GENERAL MSDS ASSISTANCE
877-276-7285

ROTELLA(R) T 15W-40 WITH ADVANCED SOOT CONTROL

EQUILON EDS: 71630E

ENVIRONMENTAL DATA SHEET



WE ARE PROVIDING OUR MOST RECENT MATERIAL SAFETY DATA SHEET AND / OR ENVIRONMENTAL DATA SHEET. IF YOU WISH TO RECEIVE UPDATES TO THIS INFORMATION, PLEASE CALL OUR GENERAL MSDS ASSISTANCE LINE (877-276-7285) TO ENSURE THAT YOU ARE ADDED TO OUR REGULAR MSDS DISTRIBUTION SYSTEM

REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, WE ASSUME NO RESPONSIBILITY FOR THE INQUIRY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, WE MAKE NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

PRODUCT NAME CHANGED; FORMERLY ROTELLA(R) T MULTIGRADE 15W-40 WITH XLIA.

SECTION XVI SPECIAL NOTES

CA = CALIFORNIA HAZ. SUBST. LIST; CA65C, CA65R, CA65C/R = CALIFORNIA SAFE DRINKING WATER AND TOXICS ENFORCEMENT ACT OF 1986 OR PROPOSITION 65 LIST; CT = CONNECTICUT TOXIC. SUBST. LIST; FL = FLORIDA SUBST. LIST; IL = ILLINOIS TOX. SUBST. LIST; LA = LOUISIANA HAZ. SUBST. LIST; MA = MASSACHUSETTS SUBST. LIST; ME = MAINE HAZ. SUBST. LIST; MN = MINNESOTA HAZ. SUBST. LIST; NJ = NEW JERSEY HAZ. SUBST. LIST; PA = PENNSYLVANIA HAZ. SUBST. LIST; RI = RHODE ISLAND HAZ. SUBST. LIST.

ZINC COMPOUND

NONE 1-2

CT, FL, IL, LA, MA, NJ, PA, RI

STATE LISTED COMPONENT CAS NO PERCENT STATE CODE

PRODUCT CODE: 50012

SECTION I PRODUCT COMPOSITION

NO. COMPOSITION CAS PERCENT

P	ROTELLA T 15W-40 WITH ADVANCED SOOT CONT	MIXTURE	100
1	HIGHLY REFINED PETROLEUM OIL	MIXTURE*	70-80
2	ADDITIVES CONTAINING:	MIXTURE	20-30
2A	ZINC COMPOUND	MIXTURE	1-2
* MAY CONTAIN: 64742-54-7			

SECTION II SARA TITLE III INFORMATION

NO. EHS RQ EHS TPQ SEC-313 313 CATEGORY 311/312 CATEGORY

2A YES ZINC COMPOUND

- *1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC 302
- *2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC 302
- *3 = TOXIC CHEMICAL, SEC 313
- *4 = CATEGORY AS REQUIRED BY SEC 313 (40 CFR 372.65 C), MUST BE USED ON TOXIC RELEASE INVENTORY FORM
- *5 = CATEGORY (FOR AGGREGATE REPORTING REQUIREMENTS UNDER SARA 311, 312)
- HEALTH: H-1 = IMMEDIATE (ACUTE) HEALTH HAZARD
- H-2 = DELAYED (CHRONIC) HEALTH HAZARD
- PHYSICAL: P-3 = FIRE HAZARD
- P-4 = SUDDEN RELEASE OF PRESSURE HAZARD
- P-5 = REACTIVE HAZARD

SECTION III ENVIRONMENTAL RELEASE INFORMATION

THIS PRODUCT IS COVERED BY EPA'S COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA) PETROLEUM EXCLUSION. THEREFORE, RELEASES TO AIR, LAND, OR WATER ARE NOT REPORTABLE UNDER CERCLA ("SUPERFUND"). HOWEVER, UNDER SECTION 311 OF EPA'S CLEAN WATER ACT (CWA), THIS PRODUCT IS CONSIDERED AN OIL. AS SUCH, SPILLS INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER, 800-424-8802. THIS PRODUCT IS AN OIL UNDER 49 CFR (DOT) PART 130. IF SHIPPED BY RAIL OR HIGHWAY IN A TANK WITH A CAPACITY OF 3,500 GALLONS OR MORE, IT IS SUBJECT TO THE REQUIREMENTS OF PART 130. MIXTURES OR SOLUTIONS IN WHICH THIS PRODUCT IS PRESENT AT 10% OR MORE MAY ALSO BE SUBJECT TO THIS RULE.

SECTION IV RCRA INFORMATION

IF THIS PRODUCT BECOMES A WASTE, IT WOULD NOT BE A HAZARDOUS WASTE BY RCRA

